

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



528238

(43) International Publication Date  
25 November 2004 (25.11.2004)

PCT

(10) International Publication Number  
**WO 2004/102283 A1**

(51) International Patent Classification<sup>7</sup>: **G03G 15/08,**  
15/043

(21) International Application Number:  
PCT/JP2004/006918

(22) International Filing Date: 14 May 2004 (14.05.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
2003-135766 14 May 2003 (14.05.2003) JP

(71) Applicant (for all designated States except US): **CANON  
KABUSHIKI KAISHA** [JP/JP]; 30-2, Shimomaruko  
3-chome, Ohta-ku, Tokyo 146-8501 (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **NAITO, Nori-**  
**hito** [JP/JP]; 1431-51-114, Ohoka, Numazu-shi,  
Shizuoka 410-0022 (JP). **YAMAUCHI, Kazumi**


[JP/JP]; 74-1-2-305, Shimotogari, Nagaizumicho,  
Suntoh-gun, Shizuoka 411-0943 (JP). **OTOMO, Ya-**  
**sunao** [JP/JP]; 6-28-2-502, Minamihoncho, Mishima-shi,  
Shizuoka 411-0841 (JP). **HASEGAWA, Hideaki** [JP/JP];  
818-2-403, Izushimata, Susono-shi, Shizuoka 410-1123  
(JP). **OSHIMA, Nobuo** [JP/JP]; 483-615, Shimotogari,  
Nagaizumicho, Suntoh-gun, Shizuoka 411-0943 (JP).

(74) Agent: **YAMADA, Ryuichi**; Toko International Patent Of-  
fice, Hasegawa Building 4F, 7-7, Toranomon 3-chome, Mi-  
nato-ku, Tokyo 105-0001 (JP).

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG,  
KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG,  
MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH,  
PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN,  
TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

[Continued on next page]

(54) Title: IMAGE FORMING APPARATUS, CARTRIDGE, AND STORING DEVICE MOUNTED TO THE CARTRIDGE



(57) Abstract: An image forming apparatus has a first image formation mode A for forming an image (502) on an image bearing member by using developer under a first predetermined image forming condition and a second image formation mode B for forming an image (507) on an image bearing member by using developer under a second image forming condition which is different from the first predetermined image forming condition regarding, eg. exposure energy and bias voltages for charging and developing, and is set so that an amount of consumption of developer with respect to an identical image in the second image formation mode is smaller than that in the first image formation mode, the apparatus includes storing means (50,103) for storing information on an amount of usage of the image bearing member i.e. wear, and control means (105) for changing the second image forming condition in the second image formation mode depending on the information stored in the storing means.



(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— with international search report

-1-

## DESCRIPTION

IMAGE FORMING APPARATUS, CARTRIDGE,  
AND STORING DEVICE MOUNTED TO THE CARTRIDGE

5

## [TECHNICAL FIELD]

The present invention relates to an image forming apparatus, particularly an image forming apparatus of electrophotography type, such as a laser beam printer or the like. The present invention also relates to a cartridge therefore and a storing device to be mounted to the cartridge.

## [BACKGROUND ART]

15 Description will be made with reference to a conventional electrophotographic image forming apparatus such as a laser beam printer.

An ordinary the electrophotographic image forming apparatus forms an electrostatic latent image by irradiating an irradiating an electrophotographic photosensitive member, uniformly charged by a charging means, with light corresponding to image information, and visualize the electrostatic latent image as an image by supplying developer (hereinafter, referred to as "toner") as a recording material by the use of a developing means. Further, the toner image is transferred from the photosensitive member onto a

-2-

recording paper as a recording medium, and the recording paper P holding the toner is sent to a fixing device so as not to disturb the toner image, which image is then subjected to fixation under heat and pressure by the fixing device to be recorded and outputted as a permanent image on the recording paper. To the developing means, a toner container as a developer containing portion containing the toner is connected. The toner is consumed by forming the image. In many cases, the toner container, the developing means, the photosensitive member, the charging means and so on, are integrally constituted as a process cartridge (hereinafter, referred to as a "cartridge"). When the toner is consumed, a user can form again an image by replacing the cartridge with a new one.

In the cartridge, a predetermined amount of toner determined by a container volume is contained. Accordingly, the number of printable sheets by the user generally correlates with the amount of toner. Users who save the toner by reducing toner consumption to permit a larger number of printable sheets are also increased. In addition, laser beam printers having such an image formation mode, such as a low (toner) consumption mode, capable of automatically decreasing the amount of toner consumption or such a draft mode wherein printing is effected by converting image data

-3-

to be printed into low resolution image data, image data decreased in the number of gradation levels, or image data decreased in image density are also increased.

5           As a means for decreasing the toner consumption amount, it is possible to use a means for changing a developing contrast, a means for changing a laser light quantity, etc. By changing the developing contrast or the laser light source, a latent image  
10 formed on the photosensitive member is changed. As a result, a toner coverage can be reduced at the time of development.

          However, in the case where the amount of toner consumption is decreased only by the developing  
15 contrast or the laser light quantity, a thin line image or a character image has a very narrow line width to provide a poor image quality in some cases even under such a condition that a change in image quality is less conspicuous with respect to a solid  
20 black image having a large area to some extent.

          For this reason, as a means for reducing the toner consumption amount while ensuring the line width, such a control method that an image frame portion constituted by a binary image is printed at an  
25 original density but an amount of toner consumption is decreased at an inner portion of the image, is performed to permit a decrease in toner consumption

amount while ensuring the line width (e.g., Japanese Laid-Open Patent Application No. Hei 9-085993). More specifically, as shown in Figure 3, the control method effects such an image processing that an original  
5 image (image data) 301 to be printed is changed into a dither image 302 wherein a frame portion, as a concentrated pixel area like a solid black image, is printed at an original density but an inner portion is provided with distributed blank dots which are not  
10 printed or a halftone image 303 wherein an amount of emission of laser or a laser on-period is changed on a one dot unit basis.

Herein, such an image formation mode for suppressing a toner coverage by changing an amount of  
15 emission or an emission period (or emission time) of a laser on one image dot unit basis is referred to as a "low (toner) consumption mode".

However, the above-described conventional image control means is accompanied with the following  
20 problems.

The low toner consumption mode image processing method which has been conventionally used, as described above, a frame portion of a concentrated pixel portion of a resultant image is printed at an  
25 original density and the image is converted into a dither image or a halftone image at an inner portion (central portion) to reduce an amount of toner

consumption. In this case, the image processing method is uniformly adapted to all the images except for those at the frame portion. A proportion between a pattern of the dither image or a pattern of the  
5 halftone image is switched according to the use circumstances, whereby it becomes possible to provide a low consumption mode which maintains image qualities.

However, in the case of effecting a low  
10 consumption mode with the dither image, when an amount of toner consumption is intended to be further decreased compared with that in the conventional low consumption mode, there arises such a problem that a blank dot portion is very conspicuous to make an  
15 image, to be originally a solid black image, a mesh image.

Further, in the case of effecting a low consumption mode with the halftone image obtained by changing an emission time or an emission light  
20 quantity of a scanner laser, there arises such a problem that the low consumption mode is more liable to be affected by a durability change of a photosensitive layer of the photosensitive member. More specifically, with respect to an ordinary laser  
25 light in the case where the halftone treatment is not performed, there is substantially no influence by a sensitivity change due to wearing or abrasion of the

-6-

photosensitive layer caused by long-term use of the photosensitive member. However, with respect to a laser light changed in emission time or emission light quantity, a sensitivity of the photosensitive member becomes lower as the photosensitive layer becomes thinner with a progress of a durability change of the photosensitive layer, i.e., wearing or abrasion of the photosensitive member. As a result, a large density lowering and a deterioration in line width are caused to occur.

Further, it is possible to mount a density sensor for detecting a sensitivity change of the photosensitive member or an surface potential sensor for the photosensitive member to change the emission time or the emission light quantity on the basis of a detection result of the sensor, thus creating the halftone image. However, the mounting of the sensors is accompanied with a problem in terms of cost for incorporating detection circuits for the above-described sensors and a problem regarding ensuring of mounting space for mounting the sensors.

In addition, in the above-described pattern difference in area of image such as the solid black image or line width as in the conventional image control means, an amount of toner consumption required to maintain an image quality is different due to a difference in image area in response cases where the



-7-

low consumption mode with the dither image is performed, so that it is necessary to sacrifice a decrease degree of the toner consumption amount if the toner consumption amount is uniformly decreased.  
5 irrespective of image area.

[DESCRIPTION OF THE INVENTION]

In order to solve the above-described problems, the present invention has been accomplished.

10 An object of the present invention is to provide an image forming apparatus and a cartridge which are capable of reducing an amount of consumption of developer while retaining stable image qualities irrespective of an amount of usage of an image bearing  
15 member.

Another object of the present invention is to provide a storing device to be mounted to a cartridge.

According to the present invention, there is provided an image forming apparatus having a first  
20 image formation mode for forming an image on an image bearing member by using developer under a first predetermined image forming condition and a second image formation mode for forming an image on an image bearing member by using developer under a second image  
25 forming condition which is different from the first predetermined image forming condition and is set so that an amount of consumption of developer with

-8-

respect to an identical image in the second image formation mode is smaller than that in the first image formation mode, the apparatus comprising:

storing means for storing information on an amount of usage of the image bearing member, and

control means for changing the second image forming condition in the second image formation mode depending on the information stored in the storing means.

According to the present invention, there is also provided an cartridge for being detachably mountable to an image forming apparatus having a first image formation mode for forming an image on an image bearing member by using developer under a first predetermined image forming condition and a second image formation mode for forming an image on an image bearing member by using developer under a second image forming condition which is different from the first predetermined image forming condition and is set so that an amount of consumption of developer with respect to an identical image in the second image formation mode is smaller than that in the first image formation mode, the cartridge comprising:

the image bearing member, and

storing means for storing information on the cartridge, the storing means having a first storing area for storing information on an amount of usage of

the image bearing member for changing the second image forming condition.

According to the present invention, there is further provided a storing device to be mounted to a cartridge for being detachably mountable to an image forming apparatus including an image bearing member and having a first image formation mode for forming an image on an image bearing member by using developer under a first predetermined image forming condition and a second image formation mode for forming an image on an image bearing member by using developer under a second image forming condition which is different from the first predetermined image forming condition and is set so that an amount of consumption of developer with respect to an identical image in the second image formation mode is smaller than that in the first image formation mode, the storing device having:

a first storing area for storing information on an amount of usage of the image bearing member for changing the second image forming condition.

According to the present invention, there is further provided a storing device to be mounted to a cartridge for being detachably mountable to an image forming apparatus including an image bearing member and having a first image formation mode for forming an image on an image bearing member by using developer under a first predetermined image forming condition

and a second image formation mode for forming an image on an image bearing member by using developer under a second image forming condition which is different from the first predetermined image forming condition and  
5 are set so that an amount of consumption of developer with respect to an identical image in the second image formation mode is smaller than that in the first image formation mode, the storing device having:

10 a first storing area for storing information on an amount of usage of the image bearing member for changing the second image forming condition,

wherein the information for changing the second image forming condition is information which is used in the second image formation mode but is not  
15 used in the first image formation mode.

These and other objects, features and advantages of the present invention will become more apparent upon a consideration of the following description of the preferred embodiments of the  
20 present invention taken in conjunction with the accompanying drawings.

#### [BRIEF DESCRIPTION OF THE DRAWINGS]

25 Figure 1 is a schematic explanatory view for illustrating image formation according to the present invention.

Figure 2 is a schematic explanatory view for

-11-

illustrating an image forming apparatus according to the present invention.

Figure 3 is a schematic explanatory view for illustrating a conventional image processing.

5           Figure 4 is a schematic explanatory view for illustrating image formation of the present invention.

Figure 5 is a schematic explanatory view for illustrating image processing according to the present invention.

10           Figure 6 is a schematic explanatory view regarding image information in the present invention.

Figure 7 is a schematic explanatory view regarding an electric potential on a photosensitive member used in the present invention.

15           Figures 8(a), 8(b) and 8(c) are graphs showing relationships between a laser emission time and an exposure potential on a photosensitive member, between the exposure potential and a solid black density, and between the exposure potential and a line  
20 width, respectively, in the present invention.

Figure 9 is a schematic explanatory view for illustrating a measurement sample for measuring the solid black density and a line width in the present invention.

25           Figures 10(a) and 10(b) are graphs showing relationships between the number of fed sheets and the solid black image, and between the number of fed

-12-

sheets and the line width, respectively, in the present invention.

Figure 11 is a graph showing a relationship between the laser emission time and the exposure potential on the photosensitive member before and after sheet feeding in the present invention.

Figure 12 is a graph showing a relationship between the number of fed sheets and the exposure potential on the photosensitive member in the present invention.

Figure 13 is a table showing the amount of drum usage and an appropriate reference emission time in Embodiment 1.

Figure 14 is a table for illustrating switching of reference emission time on the basis of an amount of drum usage in Embodiment 1.

Figure 15(a) and 15(b) are graphs each showing an effect according to Embodiment 1.

Figure 16 is a flow chart regarding control in Embodiment 1.

Figure 17 is a table showing an appropriate laser emission time on the basis of drum usage in order to keep a line width constant in Embodiment 2.

Figure 18 is a table showing switching of appropriate laser emission times for a line image and a solid black image on the basis of drum usage in Embodiment 2.

-13-

Figures 19(a) and 19(b) are graphs each showing an effect according to Embodiment 2.

Figure 20 is a flow chart regarding control in Embodiment 2.

5           Figure 21 is a graph showing a relationship between the number of fed sheets and an exposure potential on the photosensitive drum in the present invention.

10           Figure 22 is a table showing charging bias voltage application times and drum rotation times in the present invention.

          Figure 23 is a graph showing a relationship between the number of fed sheets and a drum usage  $W$  in the present invention.

15           Figure 24 is a schematic view showing storing areas in a storing device according to the present invention.

          Figure 25 is a table showing a drum usage and an appropriate laser light quantity in Embodiment 3 of  
20 the present invention.

          Figure 26 is a table showing a threshold value and an appropriate laser light quantity in Embodiment 3.

25           Figures 27(a) and 27(b) are graphs each showing an effect of switching of laser light quantities in Embodiment 3.

          Figure 28 is a flow chart regarding control

in Embodiment 3.

Figure 29 is a graph showing a relationship between a drum usage W and a developing contrast in Embodiment 4.

5           Figure 30 is a table showing a threshold value, a charging bias application condition, and a developing bias application condition in Embodiment 4.

Figure 32 is a flow chart regarding control in Embodiment 4.

10

[BEST MODE FOR CARRYING OUT THE INVENTION]  
(Embodiment 1)

Figure 2 is a schematic sectional view showing the image forming apparatus according to  
15 threshold information of the present invention.

In Figure 2, the image forming apparatus includes a photosensitive drum 1, as an image bearing member, which is prepared by forming a photosensitive material such as an OPC or an amorphous Si on a  
20 cylindrical substrate of aluminum, nickel, or the like, and is rotationally driven by drive means A, such as a motor, in a clockwise direction of an indicated arrow a at a predetermined peripheral speed.

The image forming apparatus further includes  
25 charging means 2 for uniformly charge-treating a peripheral surface of rotating the photosensitive photosensitive drum 1 in a predetermined polarity and



-15-

a predetermined potential. In this embodiment, a contact charging device using a charge roller is used.

The image forming apparatus further includes image information exposure means 3, and in this  
5 embodiment, a laser beam scanner is used as the exposure means.

This scanner 3 includes a semiconductor laser, a polygon mirror, F- $\theta$  lens, etc., and scans and exposes the uniformly charged surface of the  
10 photosensitive drum by emitting a laser beam L which is ON/OFF controlled depending on image information sent from an unshown host apparatus, thus forming an electrostatic latent image. A developing device 4 constituting a process cartridge develops the  
15 electrostatic latent image on the photosensitive drum 1 as a toner image.

As a developing method, a jumping development, a two component development, or the like is used. In many cases, a combination of image  
20 exposure and reversal development is employed.

A transfer roller 5, having an elastic layer, as a rotating member-like contact charging member is caused to contact the photosensitive drum 1 under pressure to form a transfer nip portion N  
25 therebetween, and is rotationally driven by drive means B such as a motor, in a counterclockwise direction of an indicated arrow b at a predetermined

-16-

peripheral speed.

The toner image formed on the photosensitive drum 1 is successively electrostatically transferred onto a recording material P to be recorded (a transfer-receiving material) which is fed from a paper feed portion to the transfer nip portion N.

The recording material P fed from the paper feed portion, such as a manual paper feed portion 7 or a cassette paper feed portion 14 is, after being placed in a standby state by a pre-feed sensor 10, fed to the transfer nip portion N (image forming portion) through registration rollers 11, a registration sensor 12, and a pre-transfer guide 13.

The recording material P is fed to the transfer nip portion N, created between the photosensitive drum 1 and the transfer roller 5, in synchronism with the toner image formed on the photosensitive drum 1 by the registration sensor 12.

Further, in order to solve a double feeding problem that a plurality of recording material sheets are erroneously fed simultaneously at the time of feeding the recording material P at the paper feeding portion, separation rollers (8, 15) or the like are disposed. The recording material P passed through the transfer nip portion N where it receives the toner image, is separated from the surface of the photosensitive drum and fed to a fixing device 18

-17-

through a sheet passage 9. The fixing device 18 used in this embodiment is a film heating type fixing device consisting of a pair of pressing rollers including a heating film unit 18a and a pressure roller 18b. The recording material P holding the toner image is sandwiched and fed in a fixing nip portion TN which is a pressure-contact portion between the heating film unit 18a and the pressure roller 18b, and subjected to heat and pressure application, whereby the toner image is fixed on the recording material to become a permanent image.

The recording material P on which the toner image is fixed is guided by discharge rollers 19 to be discharged in a face-up discharge port (tray) 16 or a face-down discharge port (tray) 17.

On the other hand, the surface of the photosensitive drum after being subjected to transfer of the toner image onto the recording material P is cleaned by removing a transfer residual toner by a cleaning device 6 of the process cartridge, thus being repetitively subjected to image formation. In this embodiment, the cleaning device 6 a blade cleaning device having a cleaning blade 6a.

Then, a controller and the process cartridge of the image forming apparatus according to the present invention will be described in detail with reference to Figure 1.

-18-

An electrophotographic image forming apparatus (hereinafter, simply referred to as "(apparatus) main assembly") used in this embodiment is a laser beam printer which receives image signals from a host computer and outputs the signals as a visualized image. The apparatus is of the type wherein consumable members, such as the electrophotographic photosensitive member, the developing means, and the developer (toner), are integrally supported as a process cartridge which is detachably mountable to the apparatus main assembly.

As shown in Figure 1, an image forming apparatus controller 101 includes a (main assembly) CPU 103 as a central processing computing unit for performing image forming operation of the main assembly, an IO controller 104 for effecting communication with a storing device mounted to the cartridge, an image processing controller 105 for effecting image processing of a resultant image signal, and a laser drive controller 106 for performing emission control of a scanner laser depending on an output image signal.

In the case where a process cartridge 102 is inserted into the apparatus main assembly and then a power to the main assembly is turned on, the IO controller 104 communicates with a storing device 111 mounted to the cartridge 102 to obtain various storage

-19-

values, such as the process condition and an operating history. The resultant storage values obtained by the IO controller 104 are sent to the main assembly CPU 103, and treated with those stored in the storing device 124, and treated as data at the time of effecting image formation.

The image signal 107 sent from a computer or an image reading scanner as an image signal input unit 100 connected to the image forming apparatus is subjected to image processing, such as an edge treatment or a density adjustment, thus being treated as an image signal capable of effecting an optimum image formation.

The main assembly CPU 103 computes an optimum process condition value from the storage value obtained from the storing device 111 of the cartridge and the image signal to which image processing is completed, and forms an image at the optimum process condition value.

Further, the process cartridge 102 is prepared by integrally supporting the photosensitive drum 112 as an electrophotographic photosensitive member, a charge roller 113 as a charging means for uniformly charging the photosensitive drum 112, a developing device 114, a cleaning blade 115 as a cleaning means for cleaning the surface of the photosensitive drum 112, and a waste toner container

-20-

116 for containing a residual toner removed from the photosensitive drum 112 by the cleaning blade 115, and is detachably mounted to the apparatus main assembly.

The developing device 114 includes a toner  
5 container 117 as a developer containing portion for containing toner T as developer, a developer container 118 connected with the toner container 117, a developing roller 119 as a developing means disposed opposite to the photosensitive drum 112, a developing  
10 blade 120 as a developer regulation member for regulating a toner layer thickness, a toner container inner stirring member 121 for stirring the toner T in the toner container 117 to feed the toner T into the developer container 118, and a stirring member 122 for  
15 feeding the toner T fed from the toner container 117 to the developing roller 119.

Further, before the cartridge is used, a toner sealing member 123 is adhered between the toner container 117 and the developer container 118.

20 The toner sealing member 123 is disposed so as to prevent the toner from leaking even in the case where a strong impact is caused to occur, e.g., during transport of the cartridge, and is removed by a user immediately before the mounting of the cartridge to  
25 the main assembly.

Incidentally, in this embodiment, insulating magnetic one component toner is used as the developer.

-21-

In the storing device 111 used in this embodiment, image forming process set values, such as charging and developing bias voltage set values required for image formation and a light quantity set value of the laser as the exposure means, and amounts of usages, such as an amount of usage of the photosensitive drum and an amount of residual toner, are stored. Further, in the case where the bias voltage set value or the like is switched depending on a sheet feeding history, in the storing device 111, e.g., threshold information or a set value which is switched based on the threshold information is stored.

By using the above described structure, the photosensitive drum is uniformly charged with the charge roller by applying a bias voltage from a high-voltage application unit 200 to the charge roller in accordance with an instruction from the CPU 103, and the surface thereof is subjected to scanning exposure with laser light 109, reflected by a mirror 110 and guided to the photosensitive member, varying depending on an image signal emitted from a laser scanner 108 as an exposure means, whereby an electrostatic latent image providing an objective image information is formed. The electrostatic latent image is visualized as a toner image by attaching the toner thereto by applying a bias voltage from the high-voltage application unit 200 to the developing roller, in

-22-

accordance with an instruction from the CPU 103, to carry the toner to the photosensitive member through the developing roller.

Figure 4 is a view showing the flow of image processing and outline of the image processing will be described with reference to Figure 4.

Identical reference numeral (signs) are indicated for members (means) identical to those shown in Figure 1.

Referring to Figure 4, to a main assembly of a printer, a computer equipment 100 such as a personal computer or a host computer which transmits image information 107 such as a character (text) or graphics, is connected. The computer equipment sends the image information 107 to the printer main assembly through a signal line 404, and the sent image information 107 is sent to a main assembly CPU 103 in the printer main assembly 403 or a volatile storing device (not shown), provided in the CPU 103, for temporarily storing image data up to a period wherein an image is outputted.

When it is confirmed that all the image information 107 to be printed on one recording sheet are obtained, the printer main assembly starts a printing operation. After the start of the printing operation, the image information 107 is sent to a laser drive controller 106 through a signal line 408.



-23-

On the basis of the image information 107, the laser drive controller 108 transmits a signal for controlling emission/non-emission of laser light of a laser scanner 108 through a signal line 410, thus forming an electrostatic latent image 412 on a photosensitive member 411.

Into the image data sent from the computer equipment, an emission control code for the laser scanner is inputted every one dot which is a minimum resolution of the printer main assembly. For example, a binary data as to whether the dot is printed or not printed is stored, or a multi-level data including halftone data for gray is stored. The minimum resolution unit, i.e., one dot is referred to as one pixel.

Based on the binary or multi-level data every one pixel, an emission time or light quantity of the laser scanner 108 is controlled, whereby a potential difference of the electrostatic latent image is provided on the photosensitive member to control a toner coverage and adjust a density, thus providing a good gradation characteristic.

In an ordinary image formation mode, based on the data for each one pixel corresponding to an image signal, an amount of emission (emission time or emission light quantity) of the laser scanner 108 is controlled by the CPU 103, whereby laser emission is

caused to occur, thus forming an image on the photosensitive member through formation of a latent image.

On the other hand, there is a mode for forming an image under an image forming condition different from that in the ordinary image formation mode, i.e., a low toner consumption mode for effecting printing by further reducing an amount of toner consumption than the ordinary image formation mode to save the toner. The low toner consumption mode in this embodiment will be described with reference to Figure 5. The image processing method in this embodiment is effected on the basis of a degree of concentration of pixels in order to reduce an ununiform amount of toner consumption.

With respect to selection of the ordinary image formation mode and the low toner consumption mode, it is possible to select the modes by a switch of an operation panel (not shown) provided to the image forming apparatus or command input from an external computer (e.g., 100 of Figure 1).

Figure 5 is a diagram showing a flow of image forming processing. Identical members (means) are indicated for members (means) identical to those shown in Figure 1.

Referring to Figure 5, image information sent from an external computer 100 to a laser (beam) printer

is received by a CPU 103 of the laser printer and is stored in the CPU 103 or a storing device (not shown).

The CPU 103 makes a judgment whether printing is performed in the ordinary image formation mode or the low toner consumption mode in accordance with an instruction signal from an unshown operation panel or a command from an external computer. In the case where the printing mode is determined as the ordinary image formation mode, a image information (original image) 502 is sent to a laser drive controller 106 as shown by an arrow A. On the other hand, in the case where the printing mode is determined as the low toner consumption mode, the image information (original image) 502 is sent to an image processing controller 105 for effecting image processing. In the image processing controller 105, the original image is analyzed pixel by pixel, so that a pixel area is classified into the case of a concentrated pixel area having a small size and the case of a concentrated pixel area having a large size. In the case of the small size-concentrated pixel area, image processing is performed in a processing pattern 504 and in the case of the large size-concentrated pixel area, image processing is performed in a processing pattern 505. After the image processing to image information 506 sent to the image processing controller 105 is completed, the resultant image information is again

-26-

sent to the CPU 103 of the apparatus main assembly and is sent to the laser drive controller 106 as a processed image 507 after the image processing, thus being used for emission control.

5                Figures 6(a) and 6(b) are views for illustrating an effect of image processing in the case of reducing an amount of toner consumption.

              In Figure 6(a), there are a small area image 601 having a relatively small pixel area for  
10 development and a large area pixel 602 having a relatively large pixel area for development. These small and large area images 601 and 602 are indicated in image information 604 as a part thereof.

              Referring to Figure 6(a), a cell 603 shows  
15 one pixel and corresponds to 1/600 inch in the case of a resolution of 600 dpi. A pixel 605 indicated by "B" is a pixel to which a dot is printed by development, and a blank pixel (which is not indicated by "B") is a pixel to which a dot is not printed.

20                With respect to the concentrated pixel area 601 which is determined as the small area image in the image processing CPU 103, image processing is performed according to the image processing pattern (504 of Figure 5) for the small area image. Further,  
25 with respect to the concentrated image area 602 which is determined as the large area image, image processing is performed according to the image

processing pattern (505 of Figure 5) for the large area image.

In this embodiment, the large area-concentrated pixel area is, e.g., a concentrated pixel area having not less than 8 dots in a main-scanning direction and not less than 8 dots in a sub-scanning direction. The small area-concentrated pixel area is, e.g., a concentrated pixel area having not more than 7 dots in the main-scanning direction and not more than 7 dots in the sub-scanning direction. The determination as to the large/small area-concentrated pixel areas is not limited to the above manner but can be appropriately modified.

In image information after the image processing shown in Figure 6-b, the pixels processed as the small area image 606 are processed as a halftone gradation data (halftone) H1 (608) which does not largely lower a density. Further, the pixels processed as the large area image 607 are processed as a halftone gradation data (halftone) H2 (609) which reduces the toner consumption amount as low as possible while retaining the density. The image processing condition of the halftone H2 for processing the large area image is set so that a degree of lowering in density by the image processing condition is larger than that by the image processing condition of the halftone H1.

-28-

With reference to Figure 7, description will be made on laser emission control which is effected on the basis of formation of halftone image by analysis of binary data used in this embodiment.

5           In this embodiment, a laser emission time is controlled to generate a potential difference at an exposure portion on the photosensitive member on the basis of the emission time.

          In Figure 7, a laser emission time 701  
10   necessary to form one dot depending on the resolution of printer is shown. A solid black image is formed by causing emission 703 in succession of one dot-forming period. At this time, a potential 705 on the photosensitive member becomes an exposed light-part  
15   potential V1 708 relative to a dark-part potential Vd 707 of the photosensitive member.

          A laser emission time per one pixel which is basis necessary to form one pixel is referred to as "reference emission time" 701.

20           In the case where a laser emission time is controlled to be 50 % of the reference emission time 701, a resultant laser emission time 702 for creating one dot is as shown in an upper-light portion of Figure 7. A solid black image to which such a control  
25   that the laser emission time is controlled to be 50 % of the reference emission time, is formed by continuous emission 704 at the laser emission time

702. As a result, a potential 706 on the photosensitive member has a light-part potential  $V_l'$  709 at an exposed portion relative to the surface potential  $V_d$  707 of the photosensitive member.

5 Accordingly, a latent image potential on the photosensitive member is changed to provide a difference 710 between the exposure potentials  $V_l$  and  $V_l'$ , thus changing an amount of toner consumption. A difference between the exposure potential  $V_l$  and a DC  
10 component of a developing bias voltage is referred to as a developing contrast. Further, a difference between the dark-part potential  $V_d$  and the DC component of a developing bias voltage is referred to as a back contrast.

15 Figure 8(a) shows a relationship between the laser emission time and the exposure potential (light-part potential)  $V_l$  on the photosensitive drum (photosensitive member). The abscissa represents a degree (proportion) (%) of the laser emission time per  
20 the reference emission time. As shown in Figure 8(a), when the laser emission time is 100 % to 60 % per the reference emission period, a change in the exposure potential  $V_l$  on the photosensitive drum is small. Further, also in the case of not more than 60 % per  
25 the reference emission period, the change is small but is gradually increased with a decrease of the laser emission time.

Figure 8(b) shows a relationship between the exposure potential V<sub>I</sub> on the photosensitive drum and a solid black (image) density. As shown in Figure 8(b), the solid black density is changed non-linearly with respect to the exposure potential. Particularly, as the exposure potential V<sub>I</sub> becomes small (large in terms of an absolute value), the solid black density is abruptly decreased. Further, a satisfactory value of the solid black density is generally not less than 1.4, so that a necessary exposure potential on the photosensitive drum at this time is found to be not less than -200 V. Accordingly, the laser emission time can be reduced to about 60 % per the reference emission time as understood from Figure 8(a).

Figure 8(c) shows a relationship between the exposure potential V<sub>I</sub> on the photosensitive drum and a line (image) width. The line width in this case is determined by measuring a drawn line having a 4 dot-width (about 170  $\mu\text{m}$ ) at a resolution of 600 dpi with a microscope. As shown in Figure 8(c), it is found that the line width is moderately changed relative to the exposure potential, i.e., gradually decreased with the decrease in exposure potential V<sub>I</sub> similarly as in the case of the solid black density. Further, with respect to the 4 dot-line width (170  $\mu\text{m}$ ), a necessary line width for providing a satisfactory image quality is about 165  $\mu\text{m}$ . For this reason, in order to obtain



-31-

a line width of not less than 165  $\mu\text{m}$ , it is found that the exposure potential on the photosensitive drum is required to be not less than -180 V. Accordingly, as understood from Figure 8(a), the laser emission time  
5 can be reduced to about 80 % per the reference emission time.

As shown in the graphs (Figures 8(a) to 8(c)), the solid black density and the line width affect the exposure potential on the photosensitive  
10 drum. Particularly, the exposure potential is changed largely with respect to the solid black image. Further, it is formed that the exposure potentials for the respective images (solid black image and line image) for maintaining satisfactory image qualities  
15 are different from each other.

Figure 9 shows image data subjected to confirmation of the progression of the solid black density and the line width. As shown in Figure 9, the image data include, at a central portion on, e.g., a  
20 A4-size recording sheet, a 5 cm-square solid black image 901 for measuring the solid black density and adjacent vertical and horizontal lines 802, each having a length of 5 cm (1180 dots) and a 4 dot-width, for measuring the line width. The solid black (image)  
25 density is measured by using a reflection density measuring apparatus ("RD 918", mfd. by Macbeth Corp.) with respect to the square solid black image.

-32-

Further, the line width is determined by measuring respective line widths of the vertical and horizontal lines through a microscope and obtaining an average of these widths.

5           In this embodiment, an experiment is made on changes in solid black density and line width depending on the number of fed sheets under conditions such that the laser emission time for the large area image such as the solid black image 901 is set to 60 %  
10 and that for the small area image such as the line image 901 is set to 80 %, on the basis of the predetermined laser emission time for one dot (the reference emission time).

          In this experiment, a process speed is set to  
15 200 mm/sec and an image forming apparatus wherein 30 recording sheets (A4-size) can be continuously fed in its longitudinal direction, is used.

          The toner cartridge contains 1000 g of toner and permits the number of sheet feeding of 16000  
20 (sheets) at an amount of toner consumption of 60 mg per one sheet. A resolution of the image forming apparatus is 600 dpi and a laser emission time for one dot as a basis for creating one dot is 63 nsec in this case. The A4-size recording sheets are fed in an  
25 intermittent sheet feeding mode in which the drive of the image forming apparatus is stopped every one sheet printing. Further, in this embodiment, image

-33-

formation is performed in such a low toner consumption mode, through control of laser emission time, concentrated pixel areas are discriminated such that an area having a size of not more than 10 dots x 10 dots is determined as a small area and an area having a size of not less than 11 dots x 11 dots is determined as a large area.

The measurements of the solid black density and the line width are performed by using the image sample shown in Figure 9, and the sampling is effected every 2000 sheets. Further, in this experiment, measurement of the solid black density and the line width is performed through printing effected so as to provide the number of fed sheets (as integrated value) 1.5 times that in the case of ordinary use (with no particular decrease in amount of toner consumption) since the laser emission time per the reference emission time is set to 60 % for the large area and 80 % for the small area for the purpose of examining the progression of the solid black density and the line image in the case of employing the low consumption mode.

As a result, as shown in Figure 10(a) for the progression of solid black density and Figure 10(b) for the progression of line width, both of the solid black density and the line width are found to be decreased with an increasing number of fed sheets.

Accordingly, by using the toner cartridge after completion of the continuous printing, the laser emission time and the exposure potential on the photosensitive drum are measured. As a result, as shown in Figure 11, compared with the progression at an initial stage of sheet feeding indicated by a dotted line, the progression after completion of sheet feeding indicated by a solid line shows that the exposure potential on the photosensitive drum is increased after completion of sheet feeding. Further, it is found that the exposure potential is not substantially changed before and after the sheet feeding in the case where the laser emission time is 100 % but is largely changed at the laser emission time in the vicinity of 60 %.

Further, when the progression of the number of fed sheets and the exposure potential on the photosensitive drum is examined with respect to the solid black image considerably deteriorated in particularly image quality, as shown in Figure 12, the exposure potential is found to be substantially linearly changed with the number of fed sheets. In other words, it shows that an exposure characteristic of the photosensitive drum for the toner cartridge is changed by the sheet feeding test.

This change in exposure characteristic of the photosensitive drum is considered to be attributable

-35-

to a change in thickness of the photosensitive layer. Further, since the thickness change of the photosensitive layer is changed depending on the number of fed sheets, the exposure potential on the photosensitive drum is also found to be changed depending on the number of fed sheets. In addition, the progression of the solid black density at the laser emission time, which is considerably deteriorated as shown in Figure 8(a), of 60 % per the reference emission time is largely changed as the exposure potential on the photosensitive drum is decreased. Accordingly, the above described changes are problems peculiar to the case of employing the low consumption mode using the image processing method wherein the toner consumption amount is changed by decreasing the laser emission time other than the low consumption mode, the change in exposure potential on the image bearing member, i.e., the density change of the solid black image or the change in line width are at a level of substantially no problem.

The thickness change of the photosensitive layer is changed depending on the number of fed sheets as described above. However, the relationship between the number of fed sheets and the thickness change of the photosensitive layer is changed depending on a sheet feeding condition, such as intermittent sheet feeding or a continuous sheet feeding. This is

-36-

because the change in photosensitive layer thickness is caused by wearing or abrasion of the drum surface layer and is depending on the number of rotation of the photosensitive drum and the application time of the charging bias voltage. For this reason, in this experiment, sheet feeding is performed in the intermittent mode wherein the sheet feeding is stopped every one sheet. In this intermittent mode, the charging bias voltage is applied and the number of rotation of the photosensitive member is increased not only in a period of sheet feeding but also during pre-rotation treatment and post-rotation treatment, thus most quickly wearing the photosensitive layer in the sheet feeding test. For example, as shown in Figure 21, when the exposure potentials on the photosensitive member in the case of the intermittent sheet feeding having a higher wearing speed of the photosensitive member and the case of the continuous sheet feeding having a lower wearing speed are compared, it is found that the change in exposure potential with the number of fed sheets in the continuous sheet feeding is more moderate than the case of the intermittent sheet feeding.

Accordingly, with respect to the photosensitive layer thickness change of the photosensitive member, compared with the change with the number of fed sheets, it is appropriate that an

-37-

amount of usage of the photosensitive member (drum usage) which is the sum of the charging bias voltage application time multiplied by a wearing contribution ratio of the photosensitive layer and the drum rotation time multiplied by a wearing contribution ratio of the photosensitive layer, is used. In this embodiment, the amount of usage of the photosensitive drum correlated with the photosensitive layer thickness of the photosensitive member is employed.

The drum usage is calculated according to the following equation:

$$W = a \times Pt + b \times Dt,$$

where W represents a drum usage, Pt represents a charging bias voltage application time (period), Dt represents a rotation time (period) of the photosensitive drum, and a and b represent a contribution ratio with respect to a thickness change of the photosensitive layer.

In this embodiment, a = 1 and b = 0.5.

Further, Pt and Dt are shown in Figure 22. Referring to Figure 22, in the case of the intermittent sheet feeding, the application time (or the rotation time) is the sum of those at the time of pre-rotation, sheet feeding, and post-rotation. On the other hand, in the case of continuous sheet feeding, the application (rotation) time is the sum of those at the time of

sheet feeding and sheet feeding interval since the pre-rotation and the post-rotation are not performed.

Figure 23 shows a correlation between the number of fed sheets and drum usage (W) in the cases of the intermittent sheet feeding (higher wearing speed) and the continuous sheet feeding (lower wearing speed).

In this embodiment, the intermittent sheet feeding mode is employed as the sheet feeding mode.

10 In this embodiment, depending on the drum usage of the toner cartridge, a predetermined reference emission time (laser emission time) per one dot of a concentrated pixel is changed to effect such a control wherein the exposure potential on the  
15 photosensitive drum is kept constant irrespective of the number of fed sheets (drum usage).

In this embodiment, each of a charge ratio of a laser emission time to a reference emission time per one dot for a large area concentrated pixel area such  
20 as a solid black image and a change ratio of a laser emission time to a reference emission time per one dot for a small area concentrated pixel area such as a line image are set to a constant value irrespective of the number of fed sheets (drum usage). More  
25 specifically, the change ratio for the large area concentrated pixel area is 60 % and the change ratio for the small and a concentrated pixel area is 80 %.



Accordingly, in this embodiment, a modulation degree of laser (a charge ratio of laser emission time) is, e.g., fixed to 60 % or 80 % to change the laser emission time per one dot as a reference value, thus providing the exposure potential on the photosensitive drum with a desired value.

In this embodiment, the experimental equipments (the image forming apparatus and the cartridge) used in the above described experiment are used.

Further, the change in solid black image density depending on the number of fed sheets (drum usage) is particularly large, so that attention is directed toward the solid black image in this embodiment to make a study.

First, the laser emission time per the referential one dot (reference emission time) necessary to provide an exposure potential of -200 V on the photosensitive drum at which a solid black image has a density of not less than 1.4 at respective number of fed sheets is examined.

Measurement is made very 5000 sheets in this embodiment. As a result, the laser emission time per the referential one dot for obtaining the drum exposure potential of -200 V permitting the progression of the solid black density of 1.4 or above are shown in Figure 13. Figure 13 shows the reference

-40-

emission time per one dot in the range of the image bearing member usage of 0 to 121200. The image bearing member usage (drum usage) is not the number of fed sheet as it is but is the above-described drum  
5 usage (W).

The solid black density progression and the line width progression are examined in an actual sheet feeding test by using the reference emission time, providing the resultant solid black density of not  
10 less than 1.4, shown in Figure 13. In this sheet feeding test, six low consumption modes 1 to 6 are set as shown in Figure 14. More specifically, the six low consumption modes 1 to 6 correspond to a drum usage (image bearing member usage) of 0, 37750 (corr. to the  
15 number of fed sheets of 5000 sheets), 75500 (corr. to 10000 sheets), 113250 (corr. to 15000 sheets), 15100 (corr. to 20000 sheets), and 181200 (corr. to 25000 sheets), respectively. The reference emission time is switched at timing such that the drum usage (W)  
20 reaches the respective levels. The relationship between the low consumption modes, the drum usage levels, and the reference emission times are shown in Figure 14.

As a result, as shown in Figure 15(a), the  
25 solid black image exhibits a stable image density through the sheet feeding test (with respect to the number of fed sheets). With respect to the line width

-41-

as shown in Figure 15(b), it is possible to ensure a substantially stable progression although the line width is increased in the latter stage.

Further, the threshold information obtained  
5 in this embodiment is stored in the storing device mounted to the cartridge. For example, when the sheet feeding test is performed on the same condition, the measuring speed of the photosensitive layer varies depending on characteristics of other constituted  
10 elements in some cases. In such cases, if control is effected by using the threshold information stored in advance in ROM (not shown) in the main assembly CPU, the threshold information cannot be changed for each cartridge, so that it becomes impossible to effect a  
15 desired correction depending on the drum usage. On the other hand, if the threshold information is stored in the cartridge storing device, by storing optimum threshold information for a constitutional element of the cartridge, it becomes possible to effect optimum  
20 control which meets the wearing speed change of the photosensitive layer depending on the individual cartridge characteristic.

A flow of control in the low toner consumption mode in this embodiment will be described  
25 with reference to Figures 1, 14 and 16.

Together with a printing instruction, image information is sent from a computer or the like

-42-

connected to a printer, whereby control in the printer is started (1601).

After the CPU 103 makes judgment as to whether all the image information is received (1602),  
5 the IO controller 104 needs threshold information from the storing device mounted to the cartridge. The CPU 103 compares a drum usage with threshold information to select a low consumption mode corresponding to the threshold information of the drum usage shown in  
10 Figure 14 (1604). After the selection of the low consumption mode, the image processing (1605) is effected. Then, the image processing (1614) by the image processing controller 105 is effected in corresponding with a concentrated pixel determined  
15 from a concentrated pixel having a large area (1609), a concentrated pixel having a small area (1610), and other pixels, such as blank dots (1611). Thereafter, judgment by the CPU 103 is made as to whether there is an unprocessed image with respect to the resultant  
20 image information (1608). When completion of the image processing is confirmed (1606), image formation is effected. When the image formation is effected, a signal, for providing instructions to change the laser emission time, corresponding to a selected low  
25 consumption mode is outputted from the CPU 103 to the laser drive controller 106 to change the referential laser emission time per one dot depending on the

-43-

threshold information of the drum usage (1607) thereby to expose the photosensitive image bearing member to laser light, thus effecting image formation (1612).

Thereafter, completion processing is  
5 performed to complete all the printing operations (1613).

As described above, by changing the laser emission time per the reference emission time for one dot of the concentrated pixel on the basis of the  
10 amount of usage of drum usage (the number of fed sheets) for the cartridge to effect control such that the exposure potential on the photosensitive drum is kept constant irrespective of the drum usage (the number of fed sheets), it becomes possible to effect such a  
15 low toner consumption mode which can decrease the toner consumption amount as low as possible, irrespective of a change in drum thickness due to drum use, to stabilize image qualities.

In this embodiment, such a control that a  
20 change ratio of the laser emission time to the reference emission time per one dot of the large area concentrated pixel such as a solid black image and a change ratio of the laser emission time to the reference emission time per one dot of the small area  
25 concentrated pixel are respectively set to a constant value irrespective of the number of fed sheets (drum usage).

In this embodiment, 6 types of low consumption modes to be switched are used but it is also possible to increase appropriately the number of types of low consumption modes to effectively provide  
5 stable image qualities.

Further, the image processing is performed in each low consumption mode by classifying the concentrated pixel into those having a small area and a large area. However, it is also possible to effect  
10 further detailed classification by performing analysis more specifically.

In this embodiment, with respect to a frame portion of the concentrated pixel area, it is effective to add a sequence such that an operation for  
15 reducing the toner consumption amount is not performed.

In the present invention, conditions including the process speed, the resolution, the laser emission time, the drum usage, its calculated  
20 equation, the contribution ratio with respect to the photosensitive layer thickness used in the calculation equation, the charging bias voltage application time, and the developing bias voltage application time are not limited to those employed in this embodiment.

25 (Embodiment 2)

In Embodiment 1, by changing the referential laser emission time per one dot depending on the drum

-45-

usage, it became possible to provide a low consumption mode in which image qualities are stable. Further, in Embodiment 1, it became possible to keep the solid black image density at a value of not less than 1.4  
5 irrespective of the drum usage but there is a tendency such that the line width (progression) is increased with the drum usage.

Further, in the case of increased line width, when many line images are used or the concentrated  
10 pixel area determined as the line image is concentrated at a relatively narrow area, attention of control in Embodiment 1 is directed to the solid black image. As a result, there is a possibility that respective images, which are essentially isolated with  
15 each other, are connected with each other to cause image collapse.

Accordingly, in this embodiment, the referential laser emission time per one dot 701 (Figure 7) is kept constant but, the change ratio of  
20 the laser emission time to the reference emission time for the large area concentrated pixel area such as the solid black image and the change ratio of the laser emission time to the reference emission time for the small area concentrated pixel area such as the line  
25 width are set to be different values and are changed depending on the drum usage (the number of fed sheets).

-46-

The laser emission time per the appropriate reference emission time for the large area concentrated pixel area such as the solid black image has already been described and obtained in Embodiment 1, so that explanation thereof is omitted in this embodiment. Similarly, the control of the image forming apparatus and the explanation of the process cartridge (Figure 1), explanation of outline of the image processing (Figure 4), explanation of the image processing method, and explanation of the calculation of the photosensitive drum usage are identical to those in Embodiment 1, thus being omitted.

In this embodiment, an appropriate laser emission time for the small area concentrated pixel area such as the line image is obtained. As the small area concentrated pixel area, a 4 dot-wide line image is used similarly as in Embodiment 1. In order to obtain stable image qualities in the 4 dot-wide line image, it is necessary to ensure a line width of not less than 165  $\mu\text{m}$ . Further, it is necessary to provide an exposure potential on the photosensitive drum of not less than -180 V in order to obtain the 4 dot-wide line image having the line width of not less than 165  $\mu\text{m}$ . Accordingly, in this embodiment, through the sheet feeding test (the number of fed sheets), the laser emission time providing the drum exposure potential of not less than -180 V is measured every



5000 sheets. As a result, the laser emission time for obtaining the drum exposure potential of -180 V providing the line width progression in the range of not less than 165  $\mu\text{m}$  is as shown in Figure 17.

5 By using the laser emission time (per the reference emission time) for providing the line width of not less than 165  $\mu\text{m}$  shown in Figure 17, the line width progression in the sheet feeding test is evaluated. The change ratio (83 %: 32 nsec) of the  
10 laser emission time to the reference emission time for satisfying the line width of not less than 165  $\mu\text{m}$  at a drum usage value  $W = 75500$  (10000 sheets) is switched at time when the drum usage value  $W$  is 37750 (5000 sheets). Further, the correspondence between the  
15 number of feed sheets for switching and the laser emission time is shown in Figure 18 together with the laser emission time corresponding to the drum usage in the solid black image obtained in Embodiment 1.

As a result, as shown in Figures 19(a) and  
20 19(b), by effecting switching, it became possible to obtain satisfactory stable image qualities, irrespective of the drum usage, in terms of the solid black image density progression and the line image density progression.

25 Further, also in this embodiment, storage of threshold information in the storing device mounted to the cartridge is effective as described in Embodiment

1.

A flow of control in the low toner consumption mode in this embodiment will be described with reference to Figures 1, 18 and 20.

5           Together with a printing instruction, image information (image signal) is sent from a computer or the like connected to a printer, whereby control in the printer is started (2001).

          After the CPU 103 makes judgment as to  
10 whether all the image information is received (2002), the IO controller 104 needs threshold information from the storing device mounted to the cartridge. The CPU 103 compares a drum usage with threshold information to select a low consumption mode corresponding to the  
15 threshold information of the drum usage shown in Figure 18 (2004). After the selection of the low consumption mode, the image processing (2005) is effected. Then, the image processing (2014) by the image processing controller 105 is effected in  
20 corresponding with a concentrated pixel determined from a concentrated pixel having a large area (2009), a concentrated pixel having a small area (2010), and other pixels, such as blank dots (2011). Thereafter, judgment by the CPU 103 is made as to whether there is  
25 an unprocessed image with respect to the resultant image information (2008). When completion of the image processing is confirmed (2006), image formation

is effected. When the image formation is effected, a signal, for providing instructions to change the laser emission time, corresponding to a selected low consumption mode is outputted from the CPU 103 to the laser drive controller 106 to change the referential laser emission time per one dot depending on the threshold information of the drum usage (2007) thereby to expose the photosensitive image bearing member to laser light, thus effecting image formation (2008).

10           Thereafter, completion processing is performed to complete all the printing operations (2029).

As described above, by changing the change ratios in such a manner that the change ratio of the laser emission time to the reference emission time per one dot of the large area concentrated pixel such as a solid black image and the change ratio of the laser emission time to the reference emission time per one dot of the small area concentrated pixel are set be different from each other depending on the number of fed sheets (drum usage), it becomes possible to effect such a low toner consumption mode which can decrease the toner consumption amount as low as possible, irrespective of a change in drum thickness due to drum use, to stabilize image qualities.

15           

20           

25           

In this embodiment, 6 types of low consumption modes to be switched are used but it is

-50-

also possible to increase appropriately the number of types of low consumption modes to effectively provide stable image qualities..

Further, the image processing is performed in each low consumption mode by classifying the concentrated pixel into those having a small area and a large area. However, it is also possible to effect further detailed classification by performing analysis more specifically.

10 In this embodiment, with respect to a frame portion of the concentrated pixel area, it is effective to add a sequence such that an operation for reducing the toner consumption amount is not performed.

15 In the present invention, conditions including the process speed, the resolution, the laser emission time, the drum usage, its calculated equation, the contribution ratio with respect to the photosensitive layer thickness used in the calculation equation, the charging bias voltage application time, 20 and the developing bias voltage application time are not limited to those employed in this embodiment.

The storing device mounted to the cartridge used in Embodiments 1 and 2 will be described more specifically with reference to Figure 24 which shows a 25 conceptual diagram of a storing area (region) 2801 of the storing device used in this embodiment.

-51-

Referring to Figure 24, the storing area 2801 may, e.g., be divided into an area 2802 in which process set values necessary for image formation are stored, an area 2803 for storing sheet feed history information which increases depending on sheet feeding operation, and an area 2804 in which unique information (e.g., a serial No.) of the cartridge is stored.

The process set values stored in the area 2801 include those 2805 which are switched with use and those 2806 which are constant for some cartridges.

In the area of the process set values 2805, threshold values 2807, such as switching sheet number and the number of rotation, and switching process set values 2808 are stored.

Further, a sufficient storage area is ensured so that the area 2803 for storing data of the number of rotation of the photosensitive drum and the number of fed sheets, generated by the use of the cartridge, can sufficiently store a maximum of available values.

The threshold information for the drum usage described in Embodiments 1 and 2 is stored in, the storing (memory) area 2802 of Figure 24. At the timing when the drum usage reaches the threshold information, the control effecting the change in laser emission time is performed as described in Embodiments 1 and 2.

Incidentally, a value of the drum usage ( $W$ ) calculated according to the above described equation is updated and stored in the area 2803 (Figure 28) of the storing device, and the information thereon is  
5 spread out and compared with the threshold information stored in the area 2807 of the storing device. Based on the result thereof, the control described in Embodiments 1 and 2 may be effected at timing such that the drum usage reaches the threshold information.

10 Further, as data for calculating the drum usage ( $W$ ), it is possible to use the charging bias application time  $P_t$  and the drum rotation time  $D_t$ , which are updated and stored in the area 2803 of the storing device, and coefficients (contribution ratios)  
15 a and b which are stored in the area 2804 of the storing device.

Incidentally, the laser emission time corresponding to the threshold information may be stored in the storage area for the process set values  
20 2808 and used by reading it therefrom at a timing when the drum usage reaches the threshold information.

With respect to a manner of setting the storing areas of the storing device, it is not limited to that shown in Figure 24. For example, it may  
25 appropriately modified so that a plurality of process set values are allotted to one piece of threshold information.

## (Embodiment 3)

In Embodiment 2, the ratio of the laser emission time per the predetermined reference emission time 701 (Figure 7) per one dot is changed depending on the amount of usage of the cartridge, whereby the drum exposure potential is controlled at a constant value irrespective of the number of fed sheets. On the other hand, in this embodiment, a light quantity of the laser light is changed depending on the drum usage of the toner cartridge to keep the drum exposure potential at a constant value irrespective of the number of fed sheets. The laser light quantity refers to laser luminous energy per unit area ( $\text{mJ}/\text{m}^2$ ).

With respect to explanation of the image forming apparatus and the process cartridge (Figure 1), explanation of outline of the image processing (Figure 4), explanation of the image processing method (Figures 5 - 12), and explanation of calculation of the photosensitive drum usage, the explanations are identical to those in Embodiment 1, thus being omitted.

Also in this embodiment, the experimental equipments (the image forming apparatus and the cartridge) used in the above described experiment. Further, also in this embodiment, the solid black image density is particularly largely changed depending on the number of fed sheets (drum usage), so

-54-

that attention is directed to the solid black image density to effect evaluation.

First, in this embodiment, for each of the numbers of the fed sheets, the laser light quantity  
5 providing the drum exposure potential of not less than -200 V at which the solid black image density is not less than 1.4 is measured every 5000 sheets. As a result, the laser light quantity for obtaining the drum exposure potential of -200 V providing the solid  
10 black density progression in the range of not less than 1.4 is as shown in Figure 25.

By using the laser light quantity for obtaining the drum exposure potential of not less than -200 V required for providing the solid black density  
15 of not less than 1.4 shown in Figure 25, the solid black density progression and the line width progression in the sheet feeding test are evaluated. The laser light quantity for satisfying the solid black density of not less than 1.4 at a drum usage  
20 value  $W = 75500$  (10000 sheets) is switched at time when the drum usage value  $W$  is 37750 (5000 sheets). Further, the correspondence between the number of feed sheets for switching and the laser light quantity is shown in Figure 26.

25 As a result, as shown in Figure 27(a), the solid black image density can exhibit a stable value through the sheet feeding test.



With respect to the line image, as shown in Figure 27(b), a stable line width progression can be obtained although an increase in line width is somewhat observed in the latter stage.

5           A flow of control in the low toner consumption mode in this embodiment will be described with reference to Figures 1, 26 and 28.

          Together with a printing instruction, image information is sent from a computer or the like  
10 connected to a printer, whereby control in the printer is started (1901). After the CPU 103 makes judgment as to whether all the image information is received (1902), the IO controller 104 reads threshold information from the storing device mounted to the  
15 cartridge. The CPU 103 compared a drum usage with the threshold information (1904) to select a laser light quantity corresponding to the threshold information of the drum usage shown in Figure 26 (1907). After the selection of the laser light quantity, the image  
20 processing is effected by the image processing controller 105 (1906). Then, the image processing is effected (1914) in correspondence with a concentrated pixel area determined from a concentrated pixel area having a large area (1909), a concentrated pixel area  
25 having a small area (1910), and no printing pixel areas such as blank dots (1911). Thereafter, judgment is made as to whether there is an unprocessed image

with respect to the resultant image information  
(1908). When completion of the image processing is  
confirmed (1906), image formation is effected. When  
the image formation is effected, the photosensitive  
5 drum is exposed to laser light at the selected laser  
light quantity to perform image formation (1912).  
Thereafter, completion processing is performed to  
complete all the printing operations (1913).

In this embodiment, similarly as in  
10 Embodiments 1 and 2, the threshold information of the  
drum usage is stored in the cartridge storing device  
and control of changing the laser light quantity value  
as the image forming condition at timing when the drum  
usage reaches the threshold information.

15 The storing device has the same structure as  
that shown in Figure 24. The threshold information of  
the drum usage is stored in the storage area 2807 in  
Figure 24. Further, the laser light quantity  
corresponding to the threshold information may be  
20 stored in the storage area 2808.

Further, in this embodiment, similarly as in  
Embodiments 1 and 2, it is possible to effect the  
control performed in Embodiments 1 and 2 in such a  
manner that the drum usage  $W$  calculated from the above  
25 described calculation equation of the drum usage is  
updated and stored in the storage area 2803 of the  
storing device and its information is read out and

compared with the threshold information stored in the storage area 2807 of the storing device to effect the control at timing when the drum usage reaches the threshold information.

5           Further, similarly as in Embodiments 1 and 2, the charging bias application time  $P_t$  and the drum rotation time  $D_t$  may be updated and stored in the storage area 2803 and the coefficients  $a$  and  $b$  may be stored in the storage area 2804 to be used for the  
10 calculation of the drum usage  $W$ .

As described above, by changing the laser light quantity per one dot of the concentrated pixel depending on the drum usage (the number of fed sheets) for the cartridge, it is possible to effect such a low  
15 toner consumption mode which can keep the change in exposure potential on the photosensitive member at a constant level on the basis of the drum usage and decrease the toner consumption amount as low as possible, irrespective of a change in drum thickness  
20 due to drum use, the stabilize image qualities.

In this embodiment, 5 types of each of the laser light quantities values and threshold values to be switched are used but it is also possible to increase appropriately the number of types of laser  
25 light quantity values to effectively provide stable image qualities.

Further, the image processing is performed in

-58-

each low consumption mode by classifying the concentrated pixel into those having a small area and a large area. However, it is also possible to effect further detailed classification by performing analysis more specifically.

In this embodiment, with respect to a frame portion of the concentrated pixel area, it is effective to add a sequence such that an operation for reducing the toner consumption amount is not performed.

In the present invention, conditions including the process speed, the resolution, the laser emission time, the drum usage, its calculated equation, the contribution ratio with respect to the photosensitive layer thickness used in the calculation equation, the charging bias voltage application time, and the developing bias voltage application time are not limited to those employed in this embodiment.  
(Embodiment 4)

In Embodiment 3, even in the case where the photosensitive layer is worn depending on the drum usage to change the exposure potential on the photosensitive drum, by changing a light quantity of the laser light depending on the drum usage of the toner cartridge and switching it so as to keep the drum exposure potential at a constant value, it became possible to provide a low consumption mode providing

stable image qualities.

In this embodiment, depending on the drum usage, a developing bias voltage and a charging bias voltage are changed to keep a developing contrast at a constant value without changing a back contrast, whereby a low consumption mode stabilizing image qualities is provided.

With respect to explanation of the image forming apparatus and the process cartridge (Figure 1), explanation of outline of the image processing (Figure 4), explanation of the image processing method (Figures 5 - 12), and explanation of calculation of the photosensitive drum usage, the explanations are identical to those in Embodiment 1, thus being omitted.

Hereinbelow, this embodiment will be described.

In this embodiment, the low consumption mode and experiment conditions are identical to those described in Embodiment 1.

First, when a relationship between the drum usage and the developing contrast is examined, a DC component of the developing bias voltage is -450 V similarly as in Embodiment 1 described above. From Figure 29, it is found that the developing contrast is 250 V at an initial stage of sheet feeding, i.e., at the drum usage  $W = 0$  but is lowered to about 100 V in

-60-

the vicinity of the drum usage  $W = 18000$ .

Accordingly, the DC component of the developing bias voltage is changed depending on the drum usage so that the developing contrast is always not less than 250 V. In this case, if only the DC component of the developing bias voltage is changed, it is possible to keep the developing contrast constant but a value of the back contrast with the drum exposure potential is decreased to cause developing fog in some cases. For this reason, a DC component of the charging bias voltage is also changed together with the DC component of the developing bias voltage.

Further, even in the case where the drum exposure potential is changed, the exposure potential on the photosensitive drum which is exposed to laser light from the scanner laser is to substantially changed.

The charging bias DC component and the developing bias DC component with respect to the respective drum usage values are shown in Figure 30. By using Figure 30, the density progression in the case of effecting the sheet feeding test will be described.

As a result shown in Figures 31(a) (solid black density) and 31(b) (line width), by switching the developing contrast so as to ensure a value of not

-61-

less than 250 V while retaining the black contrast,  
the solid black density progression and the line image  
progression which have been lowered depending on the  
drum usage, can be stabilized to provide a stable  
5 image through the sheet feeding test.

A flow of control in the low toner  
consumption mode in this embodiment will be described  
with reference to Figures 1, 30 and 32.

Together with a printing instruction, image  
10 information is sent from a computer or the like  
connected to a printer, whereby control in the printer  
is started (2301). After the CPU 103 makes judgment  
as to whether all the image information is received  
(2302), the IO controller 104 reads threshold  
15 information from the storing device mounted to the  
cartridge. The CPU 103 compared a drum usage with the  
threshold information (2304) to select a developing  
bias voltage (2315) and a charging bias voltage (2307)  
which correspond to the threshold information of the  
20 drum usage shown in Figure 30 (2307). After the  
selection, the image processing is effected by the  
image processing controller 105 (2306). Then, the  
image processing is effected (2314) in correspondence  
with a concentrated pixel area determined from a  
25 concentrated pixel area having a large area (2309), a  
concentrated pixel area having a small area (2310),  
and no printing pixel areas such as blank dots (2311).

Thereafter, judgment is made as to whether there is an unprocessed image with respect to the resultant image information (2308). When completion of the image processing is confirmed (2306), image formation is effected. When the image formation is effected, the photosensitive drum is charged by the developing bias voltage selected depending on the drum usage and is exposed to laser light. By the developing contrast created by the developing bias voltage and the charging bias voltage selected depending on the drum usage, image formation is performed (2312). Thereafter, completion processing is performed to complete all the printing operations (2313).

In this embodiment, similarly as in Embodiments 1 to 3, the threshold information of the drum usage is stored in the cartridge storing device and control of changing the laser light quantity value as the image forming condition at timing when the drum usage reaches the threshold information.

The storing device has the same structure as that shown in Figure 24. The threshold information of the drum usage is stored in the storage area 2807 in Figure 24. Further, the values of the developing and charging bias voltages corresponding to the threshold information may be stored in the storage area 2808.

Further, in this embodiment, similarly as in Embodiments 1 and 2, it is possible to effect the



control performed in Embodiments 1 and 2 in such a manner that the drum usage  $W$  calculated from the above described calculation equation of the drum usage is updated and stored in the storage area 2803 of the  
5 storing device and its information is read out and compared with the threshold information stored in the storage area 2807 of the storing device to effect the control at timing when the drum usage reaches the threshold information.

10 Further, similarly as in Embodiments 1 and 2, the charging bias application time  $P_t$  and the drum rotation time  $D_t$  may be updated and stored in the storage area 2803 and the coefficients  $a$  and  $b$  may be stored in the storage area 2804 to be used for the  
15 calculation of the drum usage  $W$ .

As described above, with respect to the drum exposure potential changing depending on the drum usage (the number of fed sheets), the developing bias voltage is changed to keep the developing contrast  
20 constant. Further, the developing bias voltage is changed in order to make the developing contrast constant and at the same time, the charging bias voltage is similarly changed to change the drum exposure potential, whereby the back contrast is kept  
25 constant and the developing fog is not caused to occur. As a result, it is possible to effect the low toner consumption mode capable of retaining a stable

image.

In this embodiment, the respective values of the charging and developing bias voltages described above are not limited to the above described values.

5 Further, the threshold values, the switching timing, and the number of switching are also not limited to those described above.

The above described control methods in Embodiments 1 to 4 are directed to the low toner  
10 consumption mode, thus being not applicable to an ordinary image formation mode.

In the present invention, other than the above-described control for reducing the change in exposure potential on the photosensitive member  
15 (photosensitive drum) in the low toner consumption mode described in Embodiments 1 to 4, such a control that charging and developing conditions are switched depending on the drum usage in order to retain image qualities in the ordinary image formation mode and in  
20 the low toner consumption mode. In this case, threshold values different from those for the drum usage employed in Embodiments 1 to 4 are used for switching the charging and developing conditions.

While the invention has been described with  
25 reference to the structures disclosed herein, it is not confined to the details set forth and this application is intended to cover such modifications or

changes as may come within the purposes of the improvements or the scope of the following claims.

[INDUSTRIAL APPLICABILITY]

5           As described hereinabove, according to the present invention, by changing an image forming condition depending on an amount of usage of image bearing member (drum usage), it becomes possible to retain a stable image to decrease an amount of  
10 consumption of developer, irrespective of the drum usage.

          Further, by changing an image forming condition depending on an amount of usage of image bearing member and discrimination results of the  
15 discrimination means for discriminating the size of the concentrated pixel area to be formed, it becomes possible to retain a stable image to decrease an amount of consumption of developer, irrespective of the drum usage.

20           Further, by changing the developing condition of the developing member and the charging condition of the charging member as an image forming condition depending on an amount of usage of image bearing member, it becomes possible to retain a stable image  
25 to decrease an amount of consumption of developer, irrespective of the drum usage.

## CLAIMS

1. An image forming apparatus having a first  
image formation mode for forming an image on an image  
5 bearing member by using developer under a first  
predetermined image forming condition and a second  
image formation mode for forming an image on an image  
bearing member by using developer under a second image  
forming condition which is different from the first  
10 predetermined image forming condition and is set so  
that an amount of consumption of developer with  
respect to an identical image in the second image  
formation mode is smaller than that in the first image  
formation mode, the apparatus comprising:

15 storing means for storing information on an  
amount of usage of the image bearing member, and  
control means for changing the second image  
forming condition in the second image formation mode  
depending on the information stored in said storing  
20 means.

2. An apparatus according to Claim 1, wherein  
said image forming apparatus further comprises  
discrimination means for discriminating an image to be  
25 formed, said discrimination means changes the second  
image forming condition depending on the information  
on an amount of usage of the image bearing member

stored in said storing means, and a result of discrimination by said discrimination means.

3. An apparatus according to Claim 2, wherein  
5 said discrimination means is means for discriminating a size of a concentrated pixel area and changes the second image forming condition depending on whether the concentrated pixel area is larger or smaller than a predetermined size.

10

4. An apparatus according to any one of Claims 1  
- 3, wherein the information on an amount of usage of the image bearing member is predetermined threshold information, and said control means changes the second  
15 image forming condition when an amount of usage of the image bearing member reaches a predetermined threshold information.

5. An apparatus according to any one of Claims 1  
20 - 4, wherein said image forming apparatus further comprises exposure means for exposing the image bearing member under an exposure operation condition on the basis of image information.

25 6. An apparatus according to Claim 5, wherein the exposure operation condition is an exposure time or luminous energy of said exposure means.

-68-

7. An apparatus according to any one of Claims 1  
- 4, wherein said apparatus includes a charging member  
for electrically charging the image bearing member and  
5 a developing member for supplying the developer to the  
image bearing member, and the image forming condition  
comprises a charging condition of the charging member  
and a developing condition of the developing member.

10 8. An apparatus according to Claim 7, wherein  
the charging condition is a bias voltage applied to  
the charging member and the developing condition is a  
bias voltage applied to the developing member.

15 9. An apparatus according to any one of Claims 1  
- 8, wherein the image bearing member and said storing  
means are integrally supported to form a cartridge  
which is detachably mountable to the image forming  
apparatus.

20

10. An apparatus according to Claim 9, wherein  
the cartridge further comprises the charging member or  
the developing member.

25 11. A cartridge for being detachably mountable to  
an image forming apparatus having a first image  
formation mode for forming an image on an image

bearing member by using developer under a first predetermined image forming condition and a second image formation mode for forming an image on an image bearing member by using developer under a second image forming condition which is different from the first predetermined image forming condition and is set so that an amount of consumption of developer with respect to an identical image in the second image formation mode is smaller than that in the first image formation mode, said cartridge comprising:

the image bearing member, and  
storing means for storing information on the cartridge, said storing means having a first storing area for storing information on an amount of usage of the image bearing member for changing the second image forming condition.

12. A cartridge according to any one of Claim 11, wherein said storing means further has a second storing area for storing the amount of usage of the image bearing member.

13. A cartridge according to Claim 11 or 12, wherein the information on the amount of usage of the image bearing member is predetermined threshold information.

-70-

14. A cartridge according to any one of Claims 11  
- 13, wherein said image forming apparatus further  
comprises exposure means for exposing the image  
bearing member and the second image forming condition  
5 is an exposure operation condition of said exposure  
means.

15. A cartridge according to Claim 14, wherein  
the exposure operation condition is an exposure time  
10 or luminous energy of said exposure means.

16. An apparatus according to any one of Claims  
11 - 13, wherein said apparatus includes a charging  
member for electrically charging the image bearing  
15 member and a developing member for supplying the  
developer to the image bearing member, and the image  
forming condition comprises a charging condition of  
the charging member and a developing condition of the  
developing member.

20

17. An apparatus according to Claim 16, wherein  
the charging condition is a bias voltage applied to  
the charging member and the developing condition is a  
bias voltage applied to the developing member.

25

18. A storing device to be mounted to a cartridge  
for being detachably mountable to an image forming



-71-

apparatus including an image bearing member and having  
a first image formation mode for forming an image on  
an image bearing member by using developer under a  
first predetermined image forming condition and a  
5 second image formation mode for forming an image on an  
image bearing member by using developer under a second  
image forming condition which is different from the  
first predetermined image forming condition and is set  
so that an amount of consumption of developer with  
10 respect to an identical image in the second image  
formation mode is smaller than that in the first image  
formation mode, said storing device having:

a first storing area for storing information  
on an amount of usage of the image bearing member for  
15 changing the second image forming condition.

19. A device according to any one of Claim 19,  
wherein said storing device further has a second  
storing area for storing an amount of usage of the  
20 image bearing member.

20. A device according to Claim 18 or 19, wherein  
the information on the amount of usage of the image  
bearing member is predetermined threshold information.

25

21. A device according to any one of Claims 18 -  
20, wherein said image forming apparatus further

-72-

comprises exposure device for exposing the image bearing member and the information with respect to the second image forming condition is information on an exposure operation condition of said exposure device.

5

22. A device according to Claim 21, wherein the information on the exposure operation condition is an exposure time or luminous energy of said exposure device.

10

23. An apparatus according to any one of Claims 18 - 20, wherein said apparatus includes a charging member for electrically charging the image bearing member and a developing member for supplying the developer to the image bearing member, and the image forming condition comprises a charging condition of the charging member and a developing condition of the developing member.

20

24. An apparatus according to Claim 23, wherein the charging condition is a bias voltage applied to the charging member and the developing condition is a bias voltage applied to the developing member.

25

25. A storing device to be mounted to a cartridge for being detachably mountable to an image forming apparatus including an image bearing member and having

-73-

a first image formation mode for forming an image on an image bearing member by using developer under a first predetermined image forming condition and a second image formation mode for forming an image on an image bearing member by using developer under a second image forming condition which is different from the first predetermined image forming condition and are set so that an amount of consumption of developer with respect to an identical image in the second image formation mode is smaller than that in the first image formation mode, said storing device having:

a first storing area for storing information on an amount of usage of the image bearing member for changing the second image forming condition,

wherein the information for changing the second image forming condition is information which is used in the second image formation mode but is not used in the first image formation mode.

26. A device according to any one of Claim 26, wherein said storing device further has a second storing area for storing the amount of usage of the image bearing member.

27. A device according to Claim 25 or 26, wherein the information on an amount of usage of the image bearing member is predetermined threshold information.

-74-

28. A device according to Claim 26 or 27, wherein  
said image forming apparatus further comprises  
exposure device for exposing the image bearing member  
5 and the information with respect to the second image  
forming condition is information on an exposure  
operation condition of said exposure device.

29. A device according to Claim 28, wherein the  
10 information on the exposure operation condition is an  
exposure time or luminous energy of said exposure  
device.

30. An apparatus according to any one of Claims  
15 25 - 27, wherein said apparatus includes a charging  
member for electrically charging the image bearing  
member and a developing member for supplying the  
developer to the image bearing member, and the image  
forming condition comprises a charging condition of  
20 the charging member and a developing condition of the  
developing member.

31. An apparatus according to Claim 30, wherein  
the charging condition is a bias voltage applied to  
25 the charging member and the developing condition is a  
bias voltage applied to the developing member.






FIG. 1



**FIG. 2**

**FIG.3**





FIG. 4





ਫ. ਗ. ਯ.

6/28




FIG. 6








FIG. 7

7/28



**FIG. 8**

8/28



**FIG. 9**

9/28

**FIG. 10**

10/28




FIG. 11




FIG. 12

11/28

DRUM USAGE	REFERENCE EMISSION TIME
0	63nsec
37750	68nsec
75500	73nsec
113250	78nsec
151000	84nsec
181200	-

**FIG. 13**

LOW CONSUMPTION MODE	DRUM USAGE	REFERENCE EMISSION TIME
MODE 1	0	63nsec
MODE 2	37750	68nsec
MODE 3	75500	73nsec
MODE 4	113250	78nsec
MODE 5	151000	84nsec
MODE 6	181200	-

**FIG. 14**

12/28






FIG. 15





14/28

**FIG. 16B**

DRUM USAGE	LASER EMISSION TIME	PROPORTION TO REF. EMISSION TIME
0	28nsec	80%
37750	28nsec	80%
75500	32nsec	83%
113250	36nsec	85%
151000	40nsec	88%
181200	44nsec	90%

**FIG. 17**

MODE	DRUM USAGE	LINE IMAGE	SOLID BLACK IMAGE
MODE 1	0	80%	60%
MODE 2	105700	83%	65%
MODE 3	120800	85%	70%
MODE 4	135900	88%	75%
MODE 5	151000	90%	80%
MODE 6	166100	-	-

**FIG. 18**

16/28




FIG. 19

FIG.20A

FIG.20B

FIG.20





FIG.20A

**FIG.20B**

19/28




FIG.21

	APPLICATION TIME				CONTINUOUS TIME	INTERMITTENT TIME
	PRE-ROTATION	SHEET FEED	POST-ROTATION	SHEET INTERVAL		
Pt	2.0	1.7	2.0	1.0	2.7	5.7
Dt	2.5	1.7	2.5	1.0	2.7	6.7

(sec)

FIG.22




FIG.23




FIG.24




DRUM USAGE	LASER LIGHT QUALITY
0	2.4 mJ/m <sup>2</sup>
37750	2.4 mJ/m <sup>2</sup>
75500	2.6 mJ/m <sup>2</sup>
113250	2.8 mJ/m <sup>2</sup>
151000	3.0 mJ/m <sup>2</sup>
181200	3.2 mJ/m <sup>2</sup>

**FIG.25**

THRESHOLD	DRUM USAGE	LASER LIGHT QUALITY
TH 1	0	2.4 mJ/m <sup>2</sup>
TH 2	37750	2.6 mJ/m <sup>2</sup>
TH 3	75500	2.8 mJ/m <sup>2</sup>
TH 4	113250	3.0 mJ/m <sup>2</sup>
TH 5	151000	3.2 mJ/m <sup>2</sup>
TH 6	181200	-

**FIG.26**

22/28



BEST AVAILABLE COPY

FIG.27



**FIG. 28A**


FIG. 28A

FIG. 28B

**FIG. 28**

**FIG.28B**

25/28

**FIG.29**

THRESHOLD	DRUM USAGE	CHARGING BIAS DC COMPONENT	DEVELOPING BIAS DC COMPONENT
TH 1	0	-600V	-450V
TH 2	37750	-640V	-490V
TH 3	75500	-690V	-530V
TH 4	113250	-720V	-570V
TH 5	151000	-750V	-600V
TH 6	181200	-	-

**FIG.30**

26/28




FIG.3 1

BEST AVAILABLE COPY

FIG.32A

FIG.32B

FIG.32





FIG.32A

**FIG.32B**



# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/JP2004/006918

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 7 G03G15/08 G03G15/043

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G03G

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 583 621 A (NARUKAWA TOSHIKI) 10 December 1996 (1996-12-10)	1,2, 7-12,14, 15,18, 19,21, 22,25, 26,28,29
Y	column 1, lines 6-36; figures 2-5,6C column 4, line 7 - column 6, line 53 -----	3
X	US 2002/044786 A1 (KATO SHINJI) 18 April 2002 (2002-04-18)	18
A	'0106!, '0115! figures 10-12 ----- -/--	1-17, 19-31

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents :

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*Z\* document member of the same patent family

Date of the actual completion of the international search

22 September 2004

Date of mailing of the international search report

04/11/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Kys, W

# INTERNATIONAL SEARCH REPORT

Int'l. Application No  
PCT/JP2004/006918

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 6 324 356 B1 (INOUE YOSHIYA) 27 November 2001 (2001-11-27)	18
Y	column 1, lines 13-52; figures 1-5	3
A	column 4, line 25 - column 5, line 4	1,2, 4-17, 19-31
X	----- US 5 960 232 A (CHENG KUANGTI TED) 28 September 1999 (1999-09-28)	1,2,4, 7-13, 16-20, 23-27, 30,31
	column 1, lines 21-59; figures 1-5 column 3, line 36 - column 4, line 52 -----	

# INTERNATIONAL SEARCH REPORT

Information on patent family members

Int. l. Application No

PCT/JP2004/006918

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5583621	A	10-12-1996	JP 8054806 A	27-02-1996
			DE 69523712 D1	13-12-2001
			DE 69523712 T2	08-05-2002
			EP 0704818 A1	03-04-1996
US 2002044786	A1	18-04-2002	JP 2002116585 A	19-04-2002
US 6324356	B1	27-11-2001	JP 2001194855 A	19-07-2001
US 5960232	A	28-09-1999	NONE	